

## ARCA 304015



Sample photo

**Order symbol:** ARCA 304015  
**Product nbr:** 8120022  
**Description:** Cabinet, PC  
**Remarks:** 2-point locking

**EAN:** 6418074079336  
**EI. number:**  
 Finland: 3423119  
 Electric No. 8212091207  
 Denmark:  
 Electric No. Sweden: 2500111

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

| Dimensions:                         |                               |       |        | Accessories:    |   |
|-------------------------------------|-------------------------------|-------|--------|-----------------|---|
|                                     | Length                        | Width | Height |                 |   |
| <b>mm:</b>                          | 300                           | 400   | 150    | MPP ARCA 3040   | Mounting plate perforated (350x250x2 mm - 26x11 mm)     |
| <b>inch:</b>                        | 11.8                          | 15.7  | 5.9    | MPMP ARCA 4030  | Mounting plate multiperforated (350x250x2 mm - □3.6 mm) |
| Materials:                          |                               |       |        | MPX ARCA 4030   | Mounting plate (350x250 mm)                             |
| <b>Material:</b>                    | Polycarbonate                 |       |        | DRS ARCA 304015 | DIN rail frame set                                      |
| <b>Base colour:</b>                 | RAL 7035 -light grey          |       |        | IDS ARCA 3040   | Inner door set  |
| <b>Cover colour:</b>                | RAL 7035 -light grey          |       |        | PMK ARCA 40     | Pole mounting kit                                       |
| <b>Gasket material:</b>             | Polyurethane                  |       |        | RCS ARCA 3040   | Rain canopy set   |
| Temperatures:                       |                               |       |        | SBK ARCA 30     | Support bar kit   |
| <b>Temperature °C (short term):</b> | -40 ... 120 °C                |       |        | SBK ARCA 40     | Support bar kit   |
| <b>Temperature °C (continuous):</b> | -40 ... 80 °C                 |       |        | DSP ARCA HLS    | Door stopper ARCA, horizontal, left, small              |
| <b>Temperature °F (short term):</b> | -40 ... 250 °F                |       |        | DSP ARCA HRS    | Door stopper ARCA, horizontal, right, small             |
| <b>Temperature °F (continuous):</b> | -40 ... 175 °F                |       |        |                 |   |
| Accessories:                        |                               |       |        |                 |   |
| MPS ARCA 4030                       | Mounting plate (350x250x2 mm) |       |        |                 |   |

| Rating:  |
|--|
| Ingress Protection (EN 60529): IP66                  |
| Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C |
| Electrical insulation: Totally insulated             |
| Halogen free (DIN/VDE 0472, Part 815): 1             |
| UV resistance: UL 508                                |
| Flammability Rating: UL 746C 5V                      |
| Glow Wire Test (IEC 695-2-1) °C: 960                 |

| Certificates: |
|---------------|
| SGS Fimko     |
| Gost R        |

