

## 1. Safety Standard:

## 2. Contact Specification:

- 2.1 Contact Gap: 0.3mm Minimum.
- 2.2 Contact Resistance: Maximum 100mΩ at initial value.  
Test Current: 1A, Open Circuit Test Voltage: 6VDC.  
By using Voltage Drop Method.
- 2.3 :Contact Capacity: 40Amps at 14VDC

## 3. Coil Specification at 20 °C:

- |   | 3 VDC    | 5 VDC      | 6 VDC        | 9 VDC        | 12VDC.      | 24 VDC       |
|---|----------|------------|--------------|--------------|-------------|--------------|
| 3.1 Rated Voltage:                          |          |            |              |              |             |              |
| 3.2 ( mA± 10%)<br>Nominal Current:          | 625/526  | 378.8 /318 | 315. 8/266.7 | 210. 8/177.5 | 158.3/133.3 | 79. 2 1/66.7 |
| 3.3 (± 10%).<br>Rated Power<br>Consumption: | 1.9W1.6W |            |              |              |             |              |
| 3.4 (Ω± 10%).<br>Coil Resistance:           | 4.8/5.7  | 13.2/15.7  | 19. 0/22.5   | 42. 7/50.7   | 75.8/90     | 303. 2/360   |
- 3.5 Pull In Voltage:  $\leq$  (Contact operating voltage when voltage is gradually applied. It is 65% of the Rated Voltage) V DC
- 3.6 Drop Out Voltage:  $\geq$  (Contact breaking voltage when rated voltage is gradually reduced. It is 10% of the Rated Voltage) VDC
- 3.7 Max. Allowable Voltage: (130% of the Rated Voltage) V DC
- 3.8 Operate Time: 10 milliseconds Maximum when rated Voltage is applied.
- 3.9 Release Time: 10milliseconds.。  
10 milliseconds Maximum when rated Voltage is suddenly cut off.
- 3.10 Coil Temperature Rise: 60°C Maximum.  
Maximum Allowable Voltage is applied to Coil while no load should be applied to Contacts, then the temperature should be measured when the value is stabilized. Environment temperature should not be included in.

## 4. Electrical Characteristics:

- 4.1 Life Expectancy:

4.1.1 Electrical Life: 100,000 operations Minimum at 40A/14VDC  
Rated Voltage is applied.

4.1.2 Mechanical Life: 10,000,000 operations Minimum at No Load condition.

4.1.3 Maximum Operating Frequency: Electrical: 30 operations/minute.  
Mechanical: 300 operations/minute.

## 4.2 Dielectric Strength:

4.2.1 Between Contacts: 500VAC at Test Frequency 50/60 Hz, Leakage Current: 1mA for 1 minute.

4.2.2 Between Coil & Contact: 750VAC at Test Frequency 50/60 Hz, Leakage Current: 1mA for 1 minute.

4.3 Insulation Resistance:  $\geq 100 \text{ M}\Omega$  Minimum.  
A Voltage of 500VDC should be applied after which measurement shall be made.

## 4.4 Vibration

4.4.1 Endurance I: The Coil shall be maintained under not energized condition, double amplitude 1.5 mm, the entire frequency range changes from 10 to 55 Hz then returns to 10 Hz shall be made in 1 minute. This motion shall be applied for a period of 2 hours in each of 3 mutually perpendicular axis (a total of 6 hours) There should not be any deformations in construction and in appearance, while the Electrical Specifications should be fulfilled after the test.

4.4.2 Endurance II (Error Operation): The Coil shall be maintained under energized condition, double amplitude 1.5 mm, the entire frequency range changes from 10 to 55 Hz then returns to 10 Hz shall be made in 1 minute. This motion shall be applied for a period of 5 minutes in 3 mutually perpendicular axis. Malfunction is not allowed during the test (contact breaking time should be less than 1 millisecond) In addition, there should not be any deformations in construction and in appearance while the Electrical Specifications should be fulfilled after the test.

## 4.5 Shock:

4.5.1 Endurance I: Peak Acceleration:  $1000\text{m/s}^2$   
The Coil shall be maintained under not energized condition, 5 successive shocks shall be applied in 3 mutually perpendicular axis. There should not be any deformations in construction and in appearance while the Electrical Specifications should be fulfilled after the test.

4.5.2 Endurance II (Error Operation): Peak Acceleration:  $100\text{m/s}^2$   
The Coil should be maintained under energized condition, 2 successive shocks shall be applied in 3 mutually perpendicular axis. Malfunction is not allowed during the test (contact breaking time should be less than 1 millisecond) In addition, there should not be any deformations in construction and in appearance while the Electrical Specifications should be fulfilled after the test.

## 5. Environmental Characteristics:

### 5.1 Temperature Range:

5.1.1 Operating Temperature Range:  $-40$  to  $+85^{\circ}\text{C}$ .  
Operating temperature range is the range of ambient temperature of which the Relay can be operated continuously within operative voltage range of coil (no condensation of water drops under low temperature condition)

5.1.2 Storage Temperature Range:  $-25$  to  $+70^{\circ}\text{C}$ .  
Storage temperature range is the range of ambient temperature of which the Relay can be stored without damages (no condensation of water drops under low temperature condition). Conditions are as specified elsewhere in these specifications.

5.2 Humidity Range:  $35\sim 85\%$  RH.

### 5.3 Cold Resistance:

5.3.1 Cold Resistance in Use: Relay should be kept in temperature chamber at  $-40 \pm 2^{\circ}\text{C}$  for two hours that no current or voltage shall be supplied to Relay. Such condition shall be maintained while the rated voltage is supplied to Relay, then the Relay shall operate normally. (No condensation of water drops under low temperature condition)

5.3.2 Storage Cold Resistance: Relay should be kept in temperature chamber at  $-40 \pm 2^{\circ}\text{C}$  for 72 hours. Then the Relays shall be maintained at standard atmospheric condition for 1 to 2 hours after which measurement shall be made. Construction, Relay operation, Insulation Resistance and Dielectric Strength shall satisfy the specification requirements. (No condensation of water drops under low temperature condition)

### 5.4 Heat Resistance:

5.4.1 Heat Resistance in Use: Relay should be kept in temperature chamber at  $85 \pm 2^{\circ}\text{C}$  for two hours that rated Voltage should be supplied to Coil while rated Current should be supplied to Contacts. Such condition shall be maintained while the rated voltage is supplied to Relay, then Relay shall operate normally.

## 5.4.2 Storage Heat Resistance

Relay should be kept in temperature chamber at  $70 \pm 2^{\circ}\text{C}$  for 16 hours. Then the Relays shall be maintained at standard atmospheric condition for 1 to 2 hours after which measurement shall be made. Construction, Relay operation, Insulation Resistance and Dielectric Strength shall satisfy the specification requirements.

## 5.5 Moisture Resistance:

Relay should be kept in temperature chamber at  $40 \pm 2^{\circ}\text{C}$  (90~95% RH) for 48 hours. Then the Relays shall be maintained at standard atmospheric condition for 1 to 2 hours after which measurement shall be made. Construction, Relay operation, Insulation Resistance, Dielectric Strength shall satisfy the specification requirements.

## 6. Terminal Characteristics:

### 6.1 Terminal Strength:

A load of 5Kg should be applied to the Terminal for one minute in horizontal direction. There should not be any looseness or bending of Terminals.

### 6.2 Soldering Dip Test:

The front 3 mm of Terminal should be immersed for  $3 \pm 0.5$  seconds at  $230 \pm 5^{\circ}\text{C}$ . Soldered area must be minimum 90% of the soldering surface.

### 6.3 Soldering Heat Resistance:

When the Terminal are immersed into soldering bath at  $350^{\circ}\text{C}$  for 3 seconds, the Relay shall satisfy all electrical and mechanical specifications and must not have excessive change in outside appearance.

## 7. Weight:

Approx. 21g

## 8. Sample Test Method:

GB2828-2000 Level – General II, AQL 0.4.

## HKV3

Page: 5

### Ordering Information:

HKV3	-DC	12V	-X	D	1A	X	X
Special Request Code							G: RoHS
Mounting Termination							E: Europe
PCB							U: U.S.A.
PCB							
Contact Form							NIL: 1FormC 1A:1FormA
1B:1FormB							
Coil Power							NIL:1.6 D : 1.9W
Type Of Sealing							Nil:Flow Solder
Type							S:Plastic Sealed
Type							K :Open Type
Coil Voltag							3V 、 5V、 6V、 9V、 12V、
24V							
CoilType							

# HKV3

Page: [6](#)

DC

Type



HKV3

Dimensin (mm)


# HKV3

Page: 7

HKV3-DCX-SXE





BOTTOM VIEW  
(1C)




BOTTOM VIEW  
(1C)

HKV3-DCX-KXE





BOTTOM VIEW  
(1C)




BOTTOM VIEW  
(1C)

HKV3-DCX-SXU





BOTTOM VIEW  
(1C)




BOTTOM VIEW  
(1C)

HKV3-DCX-KXU



BOTTOM VIEW  
(1C)



BOTTOM VIEW  
(1C)

Tolerance :  $\pm 0.2$