

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 16_SMB-50-1-50/111_N

Rev.: B



Description

Right angle cable plug

Interface Standards

IEC 60169-10_MIL-STD-348A/311_CECC 22130



Technical Data

Electrical Data

Impedance 50 Ω

Interface frequency max. 4 GHz

Mechanical Data

Centre contact soldered

Outer contact crimped

Weight 0.0041 kg

Environmental Data

Operating Temperature -65 °C to 165 °C

2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact

Outer contact

Body

Insulator

Crimp ferrule

Material

Copper Beryllium Alloy

Brass

Brass

PFA / PTFE

Copper

Surface Plating

Gold Plating (Nickel underplated)

Gold Plating (Nickel underplated)

Gold Plating (Nickel underplated)

Gold Plating (without Nickel underplating)

Related Documents

Catalogue drawing

DOU-00006388

Assembly instruction

DOC-0000179160

Ordering Information

Single package

16_SMB-50-1-50/111_NE

Additional Information

Suitable cables

RG_178_B/U, RG_196_A/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG

RF Technology

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions